



Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 7012-3 (1985): X-ray tube shield, Part 3: Type SHX-3
[LITD 9: Electromagnetic Compatibility]

“ज्ञान से एक नये भारत का निर्माण”

Satyanaaranay Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartṛhari—Nītiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE



PROTECTED BY COPYRIGHT

Indian Standard
SPECIFICATION FOR
X-RAY TUBE SHIELD
PART 3 TYPE SHX 3

UDC 621.386.2/7:621.386.86



© Copyright 1986

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard
SPECIFICATION FOR
X-RAY TUBE SHIELD

PART 3 TYPE SHX 3

Electron Tubes Sectional Committee, LTDC 9

Chairman

SHRI B. S. VENUGOPALAN

Representing

Bharat Electronics Ltd, Bangalore

Members

SHRI M. V. RAMANA REDDY (*Alternate to*
 Shri B. S. Venugopalan)

DR S. S. S. AGARWALA

Central Electronics Engineering Research Institute
 (CSIR), Pilani

DR G. S. SIDHU (*Alternate*)

SHRI H. M. BHATNAGAR

Indian Television Manufacturers' Association,
 New Delhi

SHRI H. S. DUBEY

Directorate General of Technical Development,
 New Delhi

SHRI R. SOUNDHIRARAJAN (*Alternate*)

SHRI B. P. GHOSH

National Test House, Calcutta

SHRI B. C. MUKHERJEE (*Alternate*)

SHRI P. KRISHNASWAMY

Directorate General of All India Radio, New Delhi

SHRI V. N. VAIDYANATHAN (*Alternate*)

DR J. N. MAITI

West Bengal Electronics Industrial Development
 Corporation Ltd, Calcutta

SHRI V. S. MITRA

Directorate General of Civil Aviation, New Delhi

SHRI R. GHOSH (*Alternate*)

DR A. MUKHERJEE

Ministry of Defence (DGI)

SHRI A. L. KHANNA (*Alternate*)

SHRI H. S. NAGABHUSHAN

Ministry of Defence (R & D)

SHRI B. M. SHANKAR PRASAD

(*Alternate*)

SHRI K. RAGHAVAN

Teletube Electronics Pvt Ltd, Ghaziabad

DR R. C. TRIPATHI

Department of Electronics, New Delhi

SHRI GAUTAM BOSE (*Alternate*)

(*Continued on page 2*)

© Copyright 1986

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act (XIV of 1957)* and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(*Continued from page 1*)

Members

SHRI D. V. VENKATASUBBAIAH P & T Board, New Delhi
SHRI V. L. VENKATRAMAN (*Alternate*)
SHRI N. SRINIVASAN, Director General, ISI (*Ex-officio Member*)
Director (Electronics)

Representing

Secretary
SHRI PAVAN KUMAR
Deputy Director (Electronics), ISI

Panel for X-Ray Tubes, LTDC 9:P3

Convener

SHRI B. S. VENUGOPALAN Bharat Electronics Ltd, Bangalore

Members

SHRI P. V. KRISHNAN (*Alternate to* Shri B. S. Venugopalan)
COL RAJESH BAHADUR Ministry of Defence (DGI)
SHRI A. L. KHANNA (*Alternate*)
SHRI BALRAJ BHANOT Directorate General of Technical Development, New Delhi
SHRI P. V. MAMMAN (*Alternate*)
SHRI P. K. JAIN Ministry of Defence (R & D)
DR C. N. RAO Punjab Biomedicals Ltd, Chandigarh
SHRI D. N. RAO Siemens India Ltd, Bombay
SHRI R. P. RAO (*Alternate*)
SHRI M. L. SETHI IGE (India) Ltd, Bombay
SHRI D. P. TRIVEDI (*Alternate*)
SHRI J. K. SHARMA Inrays, Faridabad
SHRI G. SUBRAHMANIAN Bhabha Atomic Research Centre, Bombay

Indian Standard
**SPECIFICATION FOR
 X-RAY TUBE SHIELD**

PART 3 TYPE SHX 3

0. FOREWORD

0.1 This Indian Standard (Part 3) was adopted by the Indian Standards Institution on 20 March 1985, after the draft finalized by the Electron Tubes Sectional Committee had been approved by the Electronics and Telecommunication Division Council.

0.2 The standard IS: 7012-1973* covers the specification for X-ray tube shield, Type SHX 1 to be used with diagnostic X-ray tube with rotating anode, Type DRA 1. On reviewing, the Committee decided to include other two types of X-ray tube shields, Type SHX 2 and Type SHX 3 in this standard. The Standard has, therefore, been divided into following three parts:

- Part 1 Type SHX 1
- Part 2 Type SHX 2
- Part 3 Type SHX 3

0.3 This standard covers the requirements of X-ray tube shield, Type SHX 3 which is mainly intended to be used with diagnostic X-ray tube, Types DRA-4 and DRA-5.

0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated expressing the result of a test, shall be rounded off in accordance with IS: 2-1960†. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard (Part 3) specifies the requirements of X-ray tube shield Type SHX 3.

*Specification for X-ray tube shield.

†Rules for rounding off numerical values (revised).

2. TERMINOLOGY

2.1 For the purpose of this standard, the terms and definition given in IS:1885 (Part 4/Sec 2)-1973* shall apply.

3. TYPE DESIGNATION

3.1 The X-ray tube shield shall be designated by three letters followed by a numeral, the first two letters being acronym of shield, the third letter indicating the intended use of the shield (X for use with X-ray tubes). The numeral shall indicate the serial number of the particular type of shield.

Example : SHX 3 shall mean, X-ray tube shield Type 3.

4. DIMENSIONS

4.1 The dimensions of the X-ray tube shield shall be as given in Fig. 1.

5. REQUIREMENTS

a) Nominal peak voltage	125 kV for X-ray tube type DRA-4
	150 kV for X-ray tube type DRA-5

NOTE — This test shall be conducted by the manufacturer at a test voltage of 20 percent higher than the rated voltage. The manufacturer's certificate shall be considered sufficient for this test.

b) Total heat storage capacity	130 000 joules (1750000 HU) <i>Min</i>
c) Maximum continuous rating	
without fan	300 W (400 HU/Sec)
with fan	450 W (600 HU/Sec)
d) Maximum permissible outer wall temperature	100°C
e) Operating ambient temperature	-10°C to + 55°C
f) Distance between focal spot to diaphragm flange	for 0.6 mm spot 87 mm for 1.0 mm spot 78 mm
g) Dimensions of the lead cone aperture in the ray port	24 mm × 28 mm
h) Distance between focal spot and the aperture in the ray port lead cone	40 mm
j) Total filtration	2.5 mm Al <i>Min</i>

*Electrotechnical vocabulary: Part 4 Electron tubes, Section 2 X-ray tubes (first revision).

k) Quick start (1 sec) for 8 400 rpm approximately at 150 Hz	400 to 450 V
m) Continuous rotation	90 V to 150 V and at frequency 150 Hz

6. PROTECTION

6.1 X-ray — The tube shield shall be so designed as to afford protection against X-rays in accordance with IS:6567-1972*.

6.2 Electric Shock — The tube shield shall be so designed as to provide protection against electric shock in accordance with IS:8607 (Part 2)-1978†.

7. ADDITIONAL REQUIREMENTS

7.1 High tension receptacle on the shield shall conform to IS:6758-1972‡.

7.2 The cable used shall be in accordance with IS:6757-1972§.

7.3 The H.T. Insulating oil shall be in accordance with IS:335-1972||.

7.4 The weight of the X-ray tube shield with X-ray tube and filled with suitable insulating oil shall be 25 kg approx.

7.5 The cable port screw thread details shall be specified.


*Specification for radiation protection for an X-ray tube in a protective tube housing, operating between 10 kV and 400 kV.

†General and safety requirements for electrical equipment used in medical practice: Part 2 Protection against electric shock.

‡Dimensions for high tension receptacles for X-ray tubes.

§Dimensions for high tension cable terminations for X-ray tubes.

||Specification for new insulating oils for transformers and switchgear (*second revision*).



DIMENSIONS

L_4		L	D_1	R	L_1	L_2	α	M	N_1	N_2	L_3	D_2
21	Nom mm	—	—	—	166	152	70	—	80	40	92	—
	Max mm	486	168	136	—	—	—	125	—	—	—	202

FIG. 1 X-RAY TUBE SHIELD TYPE SHX 3



INDIAN STANDARDS INSTITUTION

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 3 31 01 31, 3 31 13 75

Telegrams: Manaksantha
(Common to all Offices)

Regional Offices:

	<i>Telephones</i>
*Western : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	6 32 92 95
†Eastern : 1/14 C. I. T. Scheme VII M. V. I. P. Road, Maniktola, CALCUTTA 700054	36 24 99
Southern : C. I. T. Campus, MADRAS 600113	41 24 42
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	{2 18 43 3 16 41

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	{2 63 48 {2 63 49
'F' Block, Unity Bldg, Narasimharaja Square, BANGALORE 560002	22 48 05
Gangotri Complex, Bhadbhada Road, T. T. Nagar, BHOPAL 462003	6 27 16
22E Kalpana Area, BHUBANESHWAR 751014	5 36 27
53/5, Ward No. 29, R.G. Barua Road, 5th Byelane, GUWAHATI 781003	—
5-8-56C L. N. Gupta Marg, HYDERABAD 500001	22 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	6 98 32
117/418 B Sarvodaya Nagar, KANPUR 208005	4 72 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
Hantex Bldg (2nd Floor), Railway Station Road, TRIVANDRUM 695001	32 27

Inspection Office (With Sale Point):

Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	5 24 35
---	---------

*Sales Office in Bombay is at Novelty Chambers, Grant Road,
Bombay 400007

†Sales Office in Calcutta is at 5 Chowinghee Approach, P. O. Princep
Street, Calcutta 700072